

ACRONYMS

The following is a list of acronyms used in this SEIS.

069	Petaluma Municipal Airport
0Q3	Sonoma Valley Airport
0Q9	Sonoma Skypark
3D	Three-Dimensional
AAAE	American Association of Airport Executives
AANG	Arizona Air National Guard
AC	Advisory Circular
ACCRI	Aviation Climate Change Research Initiative
ACHP	Advisory Council on Historic Preservation
ACIP	Airports Capital Improvement Program
ACM	Asbestos Containing Material
AEDT	Aviation Environmental Design Tools
AEM	Area Equivalent Method
AGL	Above Ground Level
AIM	Aeronautical Information Management
AIP	Airport Improvement Program
ALP	Airport Layout Plan
ANCA	Airport Noise and Capacity Act of 1990
APC	Napa County Airport
APE	Area of Potential Effect
APU	Auxiliary Power Unit
AQCR	Air Quality Control Region
ARDF	Airport Research and Development Foundation
ARFF	Aircraft Rescue and Fire Fighting
ART	Adapting to Rising Tides
ASA	Airport Service Area
ASCE	American Society of Civil Engineers
ASNA	Aviation Safety and Noise Abatement Act
AST	Aboveground Storage Tank
ATC	Air Traffic Control
ATCM	Asbestos Airborne Toxic Control Measure Plan
ATCT	Airport Traffic Control Tower
AvGas	Low-lead aviation gasoline
BAAQMD	Bay Area Air Quality Management District
BAT	Best Available Technology Economically Achievable
BCA	Benefit Cost Analysis
BCDC	San Francisco Bay Conservation and Development Commission
BCFE	Billion Cubic Feet
BCT	Best Conventional Pollutant Control Technology
BFC-IP	Bayfront Conservation – Industrial Planned District
BFC - OA	Bayfront Conservation – Open Space
BMPs	Best Management Practices
BOD	Biochemical Oxygen Demand
BTU	British Thermal Units

ACRONYMS

BUSTR	The Bureau of Underground Storage Tanks Regulations
CA35	San Rafael Airport
CA LCC	California Landscape Conservation Cooperation
CAA	Clean Air Act
CAAQS	California Ambient Air Quality Standards
Cal/OSHA	California Occupational Safety and Health Administration
CalEEMod	California Emissions Estimator Model
Caltrans	California Department of Transportation
CASCaDE	Computational Assessments of Scenarios of Change for the Delta Ecosystem
CCAMP	California Costal Analysis and Mapping Project
CCR	California clapper rail
CCR	Buchanan Field Airport
CDFW	California Department of Fish and Wildlife – formerly known as the California Department of Fish and Game.
CEPA	California Environmental Protection Agency
CEQ	Council on Environmental Quality
CEQA	California Environmental Quality Act
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
CERFA	Community Environmental Response Facilitation Act
CESA	California Endangered Species Act
CFP	California Fully Protected
CFR	Code of Federal Regulations
CFS	Cubic Feet per Second
CGS	California Geological Survey
CH ₄	Methane
CHP	California Highway Patrol
CIWMB	California Integrated Waste Management Board
CIWMP	California Integrated Waste Management Plan
CNDDB	California Natural Diversity Data Base
CNEL	Community Noise Equivalent Level
CNPS	California Native Plant Society
CO	Carbon Monoxide
CO ₂ e	Carbon Dioxide Equivalencies
CO-CAT	Coastal and Ocean Resources Working Group for the California Climate Action Team
COD	Chemical Oxygen Demand
COI	Change of Information
CR	California State Rare
CRHR	California Register of Historic Resources
CRR	California Ridgway's rail
CSC	California Species of Special Concern
Cu	Copper
CWA	Clean Water Act (Federal Water Pollution Control Act, as amended)

ACRONYMS

CWRCB	California Water Resources Control Board
CY	Cubic Yards
CZMA	Coastal Zone Management Act
Day	7:00 am to 9:59 pm
dB	Decibel
dBA	A-weighted decibel
DOT	Department of Transportation
DNL	Day-Night Average Sound Level
DSA	Detailed Study Area
DVO	Gross Field Airport
EA	Environmental Assessment
EDDA	Environmental Due Diligence Audits
EDMS	Emission & Dispersion Modeling System
EDR	Environmental Data Resources
EFH	Essential Fish Habitat
EIR	Environmental Impact Report
EIS	Environmental Impact Statement
EO	Executive Order
ESA	Federal Endangered Species Act
FAA	Federal Aviation Administration
FBO	Fixed-Base Operator
FEMA	Federal Emergency Management Agency
FICON	Federal Interagency Committee on Noise
FICUN	Federal Interagency Committee on Urban Noise
FIGR	Federated Indians of Graton Rancheria
FIP	Federal Implementation Plan
FIRM	Flood Insurance Rate Maps
FPPA	Farmland Protection Policy Act
Ft ³	Cubic Feet
FY	Fiscal Year
GA	General Aviation
GAO	General Accounting Office
GHG	Greenhouse Gas
GIS	Geographic Information System
GMP	Group Stormwater Monitoring Plan
GPS	Global Positioning System
GSA	General Study Area
GSE	Ground Support Equipment
GWh	Gigawatt hours
GWP	Global Warming Potential
H ₂ O	Water Vapor
HAF	Half Moon Bay Airport
HAP	Hazardous Air Pollutant
HEPA	High-Efficiency Particulate Air
HHS	Health and Human Services
HOV	High Occupancy Vehicle

ACRONYMS

HR	Hydrologic Region
HST	Central Valley High-Speed Train
HSWA	Hazardous and Solid Waste Amendments of 1984
HUD	U.S. Department of Housing and Urban Development
HVAC	Heating, Ventilating, and Air Conditioning
HWD	Hayward Executive Airport
ICAO	International Civil Aviation Organization
IFR	Instrument Flight Rules
ILS	Instrument Landing System
IND	Industrial
INM	Integrated Noise Model
IPCC	Intergovernmental Panel on Climate Control
ISR	Indirect Source Review
Jet A	Jet fuel
JPA	Joint Power Authority
km	Kilometers
kWh	Kilowatt Hours
LEA	Local Enforcement Agency
Leq	Equivalent Sound Level
LL	Low-Lead
Lmax	Maximum Noise Level
LOC	Localizer
LOS	Level of Service
LSAA	Lake and Streambed Alteration Agreement
LTO	Landing and Takeoff Cycle
LWCA	Land and Water Conservation Act
LWCF	Land and Water Conservation Fund
MA	Metropolitan Area
MBTA	Federal Migratory Bird Treaty Act
MBTRA	Migratory Bird Treaty Reform Act
MCE	Marin Clean Energy
MCP	Marin Countywide Plan of 2007
MGD	Million Gallons per Day
mg/L	Milligrams per liter
MMBtu	Million British thermal units
MMCF	Million Cubic Feet
MMRP	Mitigation Monitoring and Reporting Program
MOA	Memorandum of Agreement
MOU	Memorandum of Understanding
MSA	Metropolitan Statistical Area
MSL	Mean Sea Level
MSN	Marin Sonoma Narrow
MSWLF	Municipal Solid Waste Landfill Units
MTOW	Maximum Take Off Weight
MW	Megawatts

ACRONYMS

N ₂ O	Nitrous Oxide
NAAQS	National Ambient Air Quality Standards
NAHC	Native American Heritage Commission
NAVAIDs	Navigational Aids
NB	Northbound
NCDC	National Climatic Data Center
NCRA	North Coast Rail Authority
NEM	Noise Exposure Map
NEPA	National Environmental Policy Act of 1969
NFA	No Further Action
NFD	Novato Fire District
NFIP	National Flood Insurance Program
NFPA	National Fire Protection Association
NHPA	National Historic Preservation Act
Ni	Nickel
Night	10:00 pm to 6:59 am
NLR	Noise Level Reduction
NMFS	National Marine Fisheries Service
NMWD	North Marin Water District
NO ₂	Nitrogen Dioxide
NO _x	Nitrogen Oxides
NOA	Naturally Occurring Asbestos
NOAA	National Oceanic and Atmospheric Administration
NOD	Notice of Determination
NOI	Notice of Intent
NOP	Notice of Preparation
NPDES	National Pollution Discharge Elimination System
NPIAS	National Plan of Integrated Airport Systems
NPL	National Priorities List
NPS	National Park Service
NRC	National Response Center Research Council
NRCS	Natural Resources Conservation Service
NRHP	National Registry of Historic Places
NRI	Nationwide Rivers Inventory
NSD	Novato Sanitary District
NSHMP	National Seismic Hazard Mapping Project
NWSFO	National Weather Service Forecast Office
O ₃	Ozone
O88	Rio Vista Municipal Airport
O&D	Origin & Destination (passengers)
OAG	Official Airline Guide
OAK	Oakland International Airport
OHWM	Ordinary High Water Mark
OS	Open Space
OSHA	Occupational Safety and Health Administration
OTR	Ozone Transport Region

ACRONYMS

P	Phosphorous
PAPI	Precision Approach Path Indicator
Pb	Lead
PFC	Passenger Facility Charges
PG&E	Pacific Gas & Electric
PM	Particulate Matter (PM ₁₀ & PM _{2.5})
PPA	Pollution Prevention Act
PRBO	Point Reyes Bird Observatory
RC	Recreational Commercial
RCR	Resort and Commercial Recreation District
RCRA	Resource Conservation and Recovery Act
Refuge	San Francisco Bay National Wildlife Refuge
RHA	Rivers and Harbors Act
RLI	Redwood Landfill and Recycling Center, Inc.
ROA	Record of Approval (issued by FAA on a Part 150 Noise Compatibility Program)
ROD	Record of Decision (issued by FAA on an EIS)
ROG	Reactive Organic Gases
ROWD	Report of Waste Discharge
RPZ	Runway Protection Zone
RQ	Reportable Quantity
RSA	Runway Safety Area
RVR	Runway Visual Range
RWQCB	Regional Water Quality Control Board
SARA	Superfund Amendments and Reauthorization Act
SB	Southbound
SCA	Stream Conservation Area
SCWA	Sonoma County Water Agency
SEI	Structural Engineering Institute
SEIS	Supplement to the Final Environmental Impact Statement
SEL	Sound Exposure Level
SF ₆	Sulfur Hexafluoride
SFBJV	San Francisco Bay Joint Venture
SFBRWQCB	San Francisco Bay Regional Water Quality Control Board
SFO	San Francisco International Airport
SHPO	State Historic Preservation Office
SIC	Standard Industry Classification
SIP	State Implementation Plan
SMART	Sonoma-Marin Area Rail Transit District
SMHM	Salt Marsh Harvest Mouse
SO ₂	Sulfur Dioxide
SO _x	Sulfur Oxide
SPCC	Oil Spill Prevention Control and Countermeasure Program
SRS	Sensitive Receptor Survey
SSURGO	Soil Survey Geographic
STP	Shovel Test Probes
STS	Charles M. Schulz Sonoma County Airport

ACRONYMS

SWMAC	Solid Waste Management Advisory Council
SWMM	Stormwater Management Model
SWMMD	Solid Waste Management Districts
SWMMP	Stormwater Management Master Plan
SWPPP	Stormwater Management Pollution Prevention Plan
SWRCB	State Water Resources Control Board
SWWTP	Southerly Wastewater Treatment Plan
TAC	Toxic Air Contaminants
TAF	Terminal Area Forecast (prepared by the FAA)
TBD	To Be Determined
THPO	Tribal Historic Preservation Office
TIP	Transportation Improvement Program
TKN	Total Kjeldahl Nitrogen
TMAC	Technical Mapping Advisory Council
TMFSC	Traffic Flow Management System Counts
TN	Total Nitrogen
TOC	Total Organic Carbon
TOFA	Taxiway Object Free Areas
TOG	Total Organic Gases
TP	Total Phosphorous
TPH	Total Petroleum Hydrocarbon
TSCA	Toxic Substances Control Act of 1976
TSS	Total Suspended Solids
UCERF	Uniform California Earthquake Rupture Forecast
USACOE	U.S. Army Corps of Engineers
USC	U.S. Code
USCG	U.S. Coast Guard
USDA	U.S. Department of Agriculture
USDOJ	U.S. Department of Interior
USDOT	U.S. Department of Transportation
USEPA	U.S. Environmental Protection Agency
USFWCA	U.S. Fish and Wildlife Coordination Act
USFWS	U.S. Fish and Wildlife Service
USGS	U.S. Geological Survey
UST	Underground Storage Tank
VA	Department of Veterans Affairs
VASI	Visual Approach Slope Indicator
VCB	Nut Tree Airport
VFR	Visual Flight Rules
VOC	Volatile Organic Compounds
WCA	Water Conservation Areas
WDR	Waste Discharge Requirement
WMI	Waste Management Incorporated
Zn	Zinc

GLOSSARY OF TERMS

Air Route Traffic Control Center (ARTCC or Center) – A *Federal Aviation Administration* facility established to provide *airport traffic control* service to aircraft operating on *Instrument Flight Rules* flight plans within *controlled airspace*, principally during the en route phase of flight. When equipment capabilities and controller workload permit, certain advisory and assistance services may be provided to *Visual Flight Rules* aircraft.

Air Taxi Aircraft – A term no longer used by the *Federal Aviation Administration*, though still used by the U.S. Department of Transportation (USDOT). The *Federal Aviation Administration* uses the term “on demand” to describe those operations formerly described as “air taxi.”

Air Traffic – Aircraft operating in the air or on an airport surface, exclusive of loading ramps and parking areas.

Air Traffic Control (ATC) – An FAA service operated for the public, to ensure adequate separation of aircraft and to promote the safe, orderly, and expeditious flow of air traffic. The air traffic facility with jurisdiction over mapped and designated airspace may authorize aircraft to proceed under specified traffic conditions within *controlled airspace*.

Airport Traffic Control Tower (ATCT) – An *airport traffic control* facility established on an airport to provide for safe, orderly, and expeditious flow of air traffic arriving at and departing from an airport, including airport surface areas such as runways and taxiways.

Air Traffic Service (ATS) Routes – “ATS route,” a generic term, includes “VOR Federal airways,” “colored Federal airways,” “alternate airways,” “jet routes,” “Military Training Routes,” “named routes,” and “RNAV routes.” The term “ATS route” serves as an overall title for listing the types of routes that comprise the United States route structure.

Aircraft Approach Category – A grouping of aircraft based on a speed calculation that takes into account the stall speed in the landing configuration at maximum gross landing weight. An aircraft must fit only one category; its category determines speed minimums that must be observed for various maneuvers. For example, an aircraft which falls in *Category A*, but is circling to land at a speed in excess of 91 knots, must use the approach *Category B* minimums when circling to land. The categories are: *Category A* - Speed less than 91 knots; *Category B* - Speed 91 knots or more but less than 121 knots; *Category C* - Speed 121 knots or more but less than 141 knots; *Category D* - Speed 141 knots or more but less than 166 knots; *Category E* - Speed 166 knots or more. (See 14 CFR Part 97.)

Aircraft Classes – For the purposes of wake turbulence aircraft separation minimums, ATC classifies aircraft as (a) *Heavy* - Aircraft capable of takeoff weights of more than 255,000 pounds whether or not they are operating at this weight during a particular phase of flight, (b) *Large* - Aircraft of more than 41,000 pounds, maximum certificated takeoff weight, up to 255,000 pounds, or (c) *Small* - Aircraft of 41,000 pounds or less maximum certificated takeoff weight.

Airman's Information Manual (AIM) – A publication containing basic flight information and *air traffic control* procedures, designed primarily as a pilot's information and instructional manual for use in the *National Airspace System*.

Airport Departure Rate – A dynamic parameter specifying the number of aircraft per hour that can depart from an airport and be accepted into the airspace.

Airport Elevation – The highest point on an airport's usable runways, expressed in feet above *mean sea level*.

Airport Improvement Program (AIP) – A Federal funding program for airport improvements. AIP is periodically reauthorized by Congress with funding appropriated from the Aviation Trust Fund. Proceeds to the Aviation Trust Fund are derived from excise taxes on airline tickets, aviation fuel, etc.

Airport Layout Plan (ALP) – A scaled drawing of existing and proposed land and facilities necessary for the operation and development of the airport. The ALP shows boundaries and proposed additions to all areas owned or controlled by the airport operator for airport purposes, the location and nature of existing and proposed action, and the location on the airport of existing and proposed non-aviation areas and improvements thereon.

Airport Operations – The total takeoffs (departures) and landings (arrivals) from an airport.

Airport Reference Code (ARC) – A coding system used to relate airport design criteria to the operational and physical characteristics of the *design aircraft* intended to operate at the airport (i.e. the most critical aircraft type currently using, or projected to use, an airport, with a minimum of 500 operations per year). ARC can either be one aircraft or a group of aircraft. The first component of the ARC is a capital letter (A, B, C, D, or E with "A" being the lowest, and "E" being the highest), which refers to the aircraft approach speed in its landing configuration. The second component, which is depicted by a Roman numeral (I, II, III, IV, V, VI, with "I" being the lowest and "VI" being the highest), refers to aircraft wingspan. Together, the two components relate aircraft operational and physical characteristics to the required design criteria of various airport components, such as runway/taxiway widths, runway to taxiway separation standards, and obstacle clearance items. Under this methodology, safety margins are provided in the physical design of airport facilities.

Airport Surveillance Radar (ASR) – Approach control radar used by air traffic controllers to detect and display an aircraft's position in the airport terminal area. ASR provides range (distance) and *azimuth* (direction) information with regard to arriving or departing aircraft.

Air Traffic Service (ATS) Routes – "ATS route," a generic term, includes "VOR Federal airways," "colored Federal airways," "alternate airways," "jet routes," "Military Training Routes," "named routes," and "RNAV routes." The term "ATS route" serves as an overall title for listing the types of routes that comprise the United States route structure.

Airway – A corridor of *controlled airspace* whose centerline is established by radio *navigational aids*. Low altitude airways (between 3,000 and 18,000 feet **Mean Sea Level**) are identified by number with the letter V as a prefix. High altitude airways (above 18,000 feet *Mean Sea Level*) are known as Jet airways and are identified by number with the letter J as a prefix.

Ambient Noise – The total sum of noise from all sources in a given place and time. This is also known as *Existing Ambient Noise*. See also *Natural Ambient Noise*.

Approach Light Systems (ALS) – One of various lighting aids that may be installed on an airport. The ALS is a series of lights that provide visual guidance to landing aircraft by radiating light beams in a directional pattern, to assist the pilot when aligning aircraft with the extended runway centerline on *final approach*.

Attenuation – Acoustical phenomenon whereby *sound* energy is reduced between the noise source and the receiver. This energy loss can be attributed to atmospheric conditions, terrain, vegetation, other natural features, and man-made features (e.g., sound insulation).

A-Weighted Sound (dBA) – A system for measuring *sound* energy that is designed to represent the response of the human ear to sound. Energy at frequencies more readily detected by the human ear is more heavily weighted in the measurement, while frequencies less well detected are assigned lower weights. A-weighted *sound* measurements are commonly used in studies where the human response to *sound* is the object of the analysis.

Base Flight Segment – A flight path at right angles to the landing runway off its approach end. The base segment normally extends from the downwind segment to the intersection of the extended runway centerline.

Base Leg – A flight path at right angles to the approach of a runway end. It usually extends from the downwind leg to the intersection of the extended runway centerline.

Baseline Condition – The existing condition or conditions prior to future development, which serve as a foundation for analysis.

Building Restriction Line (BRL) – A line drawn on an *airport layout plan* that distinguishes between areas that are suitable for buildings and areas that are unsuitable. Typically, a 35-foot building height is used to ensure that all the surfaces in 14 CFR Part 77 are clear.

California Environmental Quality Act (CEQA) – California law requiring the disclosure of environmental effects of proposed projects before discretionary approval can be issued. California law requiring the disclosure of environmental effects of proposed projects before discretionary approval can be issued. CEQA is codified at Public Resources Code Section 21000 et seq.

Capacity – The FAA defines “capacity” as the “throughput rate” of an airport, i.e., the maximum number of aircraft operations that can take place in an hour.

Community Noise Equivalent Level (CNEL) – The CNEL metric is a single value of sound level for 24 hour period, which includes all of the time-varying sound energy within the period. To represent the greater annoyance caused by a noise event during the evening hours, the CNEL metric includes an added 5 dB weighting for evening noise events occurring between 7:00 P.M. and 10:00 P.M. Similarly, the CNEL metric also incorporates a 10 dB nighttime (10:00 P.M. and 7:00 A.M.) penalty to represent the greater annoyance caused by a noise event at night.

Commuter Aircraft – Generally, aircraft of designated size or seating capacity (usually nine or fewer seats) that support scheduled air transportation services for compensation or hire in air commerce, with a frequency of at least five round trip operations per week on at least one route according to a published flight schedule. Commuter aircraft operate pursuant to a *Federal Aviation Administration* air carrier certificate issued under 14 CFR Parts 119 and 135 of the *Federal Aviation Regulations*. (See 14 CFR § 119.3, *Definitions*.) **Regional Jets (RJs)** are not “commuters,” because they are large transport category aircraft and fall within the *Federal Aviation Administration’s air carrier aircraft* category.

Contour – See *Noise Contour*.

Controlled Airspace – An airspace of defined dimensions within which *air traffic control* service is provided to flights operating under both *Instrument Flight Rules* and *Visual Flight Rules* in accordance with the airspace classification. Controlled airspace designated as Class A, Class B, Class C, Class D, and Class E, generally according to altitude above the surface, distance from a primary airport, and volume of aircraft operations. Controlled airspace is also that airspace within which all aircraft operators are subject to certain pilot qualifications, operating rules, and equipment requirements (for specific operating requirements, see 14 CFR Part 91).

Crosswind Leg – A flight path at right angles to the approach runway end off of the upwind end.

Day-Night Average Sound Level (DNL) - A noise measure used to describe the average *sound* level over a 24-hour period, typically an average day over the course of a year. In computing DNL, an extra weight of ten *decibels* is assigned to noise occurring between the hours of 10:00 p.m. and 7:00 a.m. to account for increased annoyance when ambient noise levels are lower and people are trying to sleep. DNL may be determined for individual locations or expressed in noise contours.

dBA - See *A-weighted Sound Level*

Decibel (dB) - *Sound* is energy and is measured by its pressure. Because of the enormous range of *sound* pressures to which the human ear is sensitive, the raw sound pressure measurement is converted to the *decibel* scale for purposes of description and analysis. The *decibel* scale is logarithmic. A ten-*decibel* increase in *sound* is perceived as a doubling of sound (or twice as loud) by the human ear.

Declared Distances – The distance the airport owner declares available for the airplane’s takeoff run, takeoff distance, accelerate-stop distance, and landing distance requirements.

Departure Fix – A departure fix, or so-called departure gate, is a section of airspace used to separate departing from arriving aircraft. This fix determines the initial flight path and direction of the aircraft.

Design Aircraft - The most critical aircraft type currently using, or projected to use, an airport, with a minimum of 500 operations per year. It can either be one aircraft or a group of aircraft. See also *Airport Reference Code*.

Detailed Study Area - One of the areas identified for detailed environmental investigation as part of this *Environmental Impact Statement*. This *study area* is smaller in scale than the *General Study Area* to accommodate the more detailed analyses. (See *General Study Area*.)

Displaced Threshold - A threshold that is located at a point on the runway other than the designated beginning of the runway. The portion of pavement behind a displaced threshold may be available for takeoffs in both directions and landings from the opposite direction.

Distance Measuring Equipment (DME) - A flight instrument that measures the line-of-sight distance of an aircraft from a navigational radio station in *nautical miles*.

Downwind Approach/Arrival – A flight path parallel to the landing runway in the direction opposite to landing.

Easement - The legal right of one party to use part of the rights of a piece of real estate belonging to another party. This may include, but is not limited to, the rite of passage over, on or below the property; certain air rights above the property, including view rights; and the rights to any specified form of development or activity.

Engine Run-ups – A routine procedure for testing aircraft systems by running one or more engines at a high power setting. Engine run-ups are normally conducted by airline maintenance personnel checking an engine or other on board systems following maintenance.

Enplanements - The number of revenue passengers boarding an aircraft at an airport.

EnRoute Air Traffic Control System - Unlike *airport traffic control tower* or terminal radar approach control service, *Air Route Traffic Control Centers* provide en route service, generally for aircraft on *Instrument Flight Rules* flight plans, when these aircraft are operating between departure and destination airports at designated higher altitudes. When equipment, capabilities, and controller workload permit, certain advisory/assistance services may be provided to *Visual Flight Rules* aircraft. En route airspace is that airspace not delegated to approach control.

Environmental Impact Report (EIR) – An environmental impact report is an informational document which, when its preparation is required, shall be considered by every public agency prior to its approval or disapproval of a project. The purpose of an environmental impact report is to provide public agencies and the public in general with detailed information about the effect which a proposed project is likely to have on the environment; to list ways in which the significant effects of such a project might be minimized; and to indicate alternatives to such a project.

Environmental Impact Statement (EIS) – As stated in CEQ regulation 40 CFR § 1508.11, a detailed written statement that complies with NEPA section 102 (42 USC § 4332) by including in every report on proposals for major Federal actions significantly affecting the quality of the human environment, a detailed statement on (i) environmental impact of the proposed action, (ii) any adverse environmental effects which cannot be avoided should the proposal be implemented, (iii) alternatives to the proposal, (iv) relationship between local short-term uses of the environment and maintenance and enhancement of long-term productivity, and (v) any irreversible and irretrievable commitment of resources involved in the proposed action, should it be implemented.

Equivalent Sound Level (Leq) – The *A-weighted* energy average *sound* level experienced over a given period of time. The metric is expressed as ten times the log of the total noise energy divided by the number of seconds during the period under consideration.

Federal Aviation Administration (FAA) – The FAA is the Federal agency responsible for insuring the safe and efficient use of the nation's airspace, for fostering civil aeronautics and air commerce, and for supporting the requirements of national defense. The activities required to carry out these responsibilities include: safety regulations, airspace management and the establishment, operation and maintenance of a system of **air traffic control** and navigation facilities; research and development in support of the fostering of a national system of airports, promulgation of standards and specifications for civil airports, and administration of Federal grants-in-aid for developing public airports; various joint and cooperative activities with the Department of Defense, and technical assistance (under State Department auspices) to other countries.

Federal Aviation Regulations (FAR) – The body of Federal regulations enacted by the U.S. Secretary of Transportation, under the statutory authority of the Federal Aviation Act and published in Title 14 of the Code of Federal Regulations (CFR).

Final Approach – A flight path in the direction of landing that follows the extended runway centerline. It usually extends from the **base leg** to the runway.

Fixed-Base Operator (FBO) – A business located on the airport that provides services such as hangar space, fuel, flight training, repair, and maintenance to airport users.

Fleet Mix – The mix or differing types of aircraft operating in a particular airport environment.

Flight Track Utilization – The use of established routes for arrival and departure by aircraft to and from the runways at the airport.

General Aviation Aircraft – Generally, those U.S. registered civil aircraft which operate for private and noncommercial purposes and whose operations are not governed by 14 CFR Parts 119, 121, 125, or 135 of the **Federal Aviation Regulations**. General aviation aircraft range from small single-engine propeller aircraft to large **turbojet** private aircraft.

General Study Area (GSA) – One of the areas identified for environmental investigation as part of this **EIS**. This study area is larger in scale than the **Detailed Study Area**. (See **Detailed Study Area**.)

Geographic Information Systems (GIS) – An information system that is designed for storing, integrating, manipulating, analyzing, and displaying data referenced by spatial or geographic coordinates.

Glide Slope (GS) – Provides vertical guidance for aircraft during approach and landing. The glide slope consists of the following:

Electronic components emitting signals which provide vertical guidance by reference to airborne instruments during instrument approaches such as **Instrument Landing System**, or visual ground aids, such as **Visual Approach Slope Indicator**, which provide vertical guidance for **visual flight rules** approach or for the visual portion of an **instrument approach** and landing.

GPS – Global Positioning System equipment onboard an aircraft takes advantage of various radio navigation and/or *Global Positioning System* routes to guide the aircraft. A system of satellites used as reference points to enable navigators equipped with GPS receivers to determine their latitude, longitude, and altitude.

Grid Analysis - A type of aircraft noise analysis that evaluates the noise levels at individual points rather than through generation of **noise contours**.

Ground Effect - Noise **attenuation** attributed to absorption or reflection of noise by man-made or natural features on the ground surface.

Hub - An airport that services airlines that have **hubbing** operations.

Hubbing - A method of airline scheduling that times the arrival and departure of several aircraft in a close period of time in order to allow the transfer of passengers between different flights of the same airline in order to reach their ultimate destination. Several airlines may conduct hubbing operations at an airport.

Infill - Urban development occurring on vacant lots in substantially developed areas; may also include the redevelopment of areas to a greater density.

Instrument Approach – A series of predetermined maneuvers for the orderly transfer of an aircraft under **instrument flight rules** from the beginning of the initial approach to a landing, or to a point from which a landing may be made visually.

Instrument Flight Rules (IFR) – That portion of the **Federal Aviation Regulations** (14 CFR Part 91) specifying the procedures to be used by aircraft during flight in **Instrument Meteorological Conditions**. These procedures may also be used under visual conditions and provide for **positive control** by **Air Traffic Control**. (See also **Visual Flight Rules**).

Instrument Landing System (ILS) – An electronic system installed at some airports which helps to guide pilots to runways for landing during periods of limited visibility or adverse weather.

Instrument Meteorological Conditions (IMC) – Weather conditions expressed in terms of visibility, distance from clouds, and cloud ceilings during which all aircraft are required to operate using **Instrument Flight Rules (IFR)**.

Integrated Noise Model (INM) - A computer model developed, updated and maintained by the *Federal Aviation Administration* to predict the noise exposure generated by aircraft *operations*.

Itinerant Operation - An aircraft flight that ends at an airport different from where the flight began.

Knots - Airspeed measured as the distance in *nautical miles* (6,076.1 feet) covered in one hour. (Approximately equal to 1.15 miles per hour.)

Land Use Compatibility - The ability of land uses surrounding the airport to coexist with airport-related activities with minimum conflict.

Landing and Takeoff (LTO) Cycle - The time that an aircraft is in operation at or near an airport. An LTO cycle begins when an aircraft starts its *final approach* (arrival) and ends after the aircraft has made its climb-out (departure).

Ldn - See *DNL*. Ldn is used in place of *DNL* in mathematical equations only.

Leq - See *Equivalent Sound Level*.

Local Operation - An aircraft flight that begins and ends at the same airport.

Localizer - The component of an *Instrument Landing System* that provides lateral course guidance to the runway.

Loudness - The subjective assessment of the intensity of *sound*.

Maximum Noise Level (Lmax) - The maximum *sound* pressure for a given event adjusted toward the frequency range of human hearing.

Mean Sea Level (MSL) - The average height of the surface of the sea for all stages of the tide; used as a reference for elevations; also called sea level datum.

Military Operations Area - Airspace established to separate or segregate certain non-hazardous military activities from *Instrument Flight Rules* traffic and to identify for *Visual Flight Rules* traffic where these activities are conducted.

Missed Approach - A maneuver conducted by a pilot when an *instrument approach* cannot be completed for landing at an airport. *Instrument approach* procedure charts show the route of flight and altitude that the pilot must follow in this circumstance.

National Airspace System (NAS) - The common network of U.S. airspace, air navigation facilities, equipment, services, airports, or landing areas; aeronautical charts, information, and services; rules, regulations, and procedures; technical information, manpower, and materials, all of which are used in aerial navigation to provide a safe and efficient flying environment.

National Environmental Policy Act of 1969 (NEPA) – The original legislation establishing the environmental review process for proposed Federal actions.

National Pollutant Discharge Elimination System (NPDES) – Federal requirement under the **Clean Water Act (CWA)** that any discharge of a non-point source of pollution into waters of the United States be in conformance with any established water quality management plan developed under the **Clean Water Act**.

Nautical Mile - A measure of distance equal to one minute of arc on the earth's surface (6,076.1 feet or 1,852 meters).

Natural Ambient Noise – Existing Ambient Noise, minus man made sounds. See **Ambient Noise** and **Existing Ambient Noise**.

NAVAIDs (Navigational Aids) – Any facility used by an aircraft for navigation.

Navigational Fix – A geographical position determined by reference to one or more radio navigational aids.

Noise Abatement – A measure or action that minimizes the amount of impact of noise on the environs of an airport. Noise abatement measures include aircraft operating procedures and use or disuse of certain runways or **flight tracks**.

Noise Contour – A map representing average annual noise levels summarized by lines connecting points of equal noise exposure.

Nondirectional Beacon (NDB) – A beacon transmitting non-directional signals whereby the pilot of an aircraft equipped with direction finding equipment can determine the bearing to and from the station. When the radio beacon is installed in conjunction with the **Instrument Landing System** marker, it is normally called a compass locator.

Nonprecision Approach - A standard **instrument approach** procedure providing runway alignment but no **glide slope** or descent information.

On-Demand - Generally, U.S. registered civil aircraft of designated size (usually 30 or fewer passenger seats with payload capacity of 7,500 pounds or less) that support on-demand, unscheduled, or infrequently scheduled passenger-carrying or cargo service (including public charters) for compensation or hire, pursuant to a air carrier certificate issued under 14 CFR Parts 119 and 135 of the Federal Aviation Regulations. (See 14 CFR § 119.3, Definitions.) This term includes operations formerly classified as air taxi, a term no longer used by the **Federal Aviation Administration** but still used by the U.S. Department of Transportation (USDOT).

Precision Approach Path Indicator (PAPI) - Provides visual approach slope guidance to aircraft during an approach. It is similar to a **Visual Approach Slope Indicator** but provides a sharper transition between the colored indicator lights.

Precision Approach Procedure - A standard *instrument approach* procedure in which an electronic *glide slope*/glide path is provided (e.g., *Instrument Landing System* and *Precision Approach Radar*).

Precision Approach Radar (PAR) - Navigational equipment located on the ground adjacent to the runway, consisting of one antenna, which scans the vertical plane, and a second antenna, which scans the horizontal plane. The PAR provides the controller with a picture of the descending aircraft in *azimuth*, distance, and elevation, permitting an accurate determination of the aircraft's alignment relative to the runway centerline and the *glide slope*.

Profile - The position of the aircraft during an approach or departure in terms of altitude above the runway and distance from the runway end.

Propagation - Sound propagation is the spreading or radiating of sound energy from the noise source. It usually involves a reduction in sound energy with increased distance from the source. Atmospheric conditions, terrain, natural objects, and manmade objects affect sound propagation.

Public Use Airport - An airport open to public use without prior permission, and without restrictions within the physical capabilities of the facility. It may or may not be publicly-owned.

Record of Decision (ROD) - As stated in CEQ regulation 40 CFR § 1505.2, the *Federal Aviation Administration's* findings, explanations, and related justifications after review of a Draft Environmental Assessment or *Environmental Impact Statement*. The ROD specifies the environmentally preferred alternative.

Regional Jet - A jet aircraft that falls within the air carrier aircraft category because of size and payload. For use in air commerce, the *regional jet* must be operated pursuant to an air carrier certificate pursuant to an air carrier certificate issued under 14 CFR Parts 119 and 121 of the *Federal Aviation Regulations*. (See 14 CFR § 119.3, for Domestic, Flag, and Supplemental operations). *Regional jets* are not operated as commuter aircraft pursuant to 14 CFR Part 135. *Regional jets* are typically jet aircraft, with approximately 35 to 90 seats. The next-generation *regional jets* are expected to seat 100 passengers.

Reliever Airport - An airport which, when certain criteria are met, relieves the aeronautical demand on a busier air carrier airport.

Retrofitted Aircraft - An aircraft originally certified as *Stage 2* that has been modified to meet *Stage 3* requirements. This includes both modification of engines or the replacement of engines to meet the *Stage 3* standard.

Run-up - A routine procedure for testing aircraft systems by running one or more engines at a high power setting. *Engine run-ups* are normally conducted by airline maintenance personnel checking an engine or other on board systems following maintenance.

Runway End Identifier Lights (REIL) - Two synchronized flashing lights, one on each side of the *runway threshold*, which identify the approach end of the runway.

Runway Protection Zone (RPZ) - An area, trapezoidal in shape and centered about the extended runway centerline, designated to enhance the protection of people and property on the ground. It begins 200 feet (60 M) beyond the end of the area usable for takeoff or landing. The RPZ dimensions are functions of the aircraft, type of operation, and visibility minimums. (Formerly known as the clear zone.)

Runway Safety Area (RSA) - A defined surface surrounding the runway prepared or suitable for reducing the risk or damage to airplanes in the event of an undershoot, overshoot, or excursion from the runway.

Runway Threshold - The beginning of that portion of the runway usable for landing.

Scoping - Scoping is an early and open process for determining the scope or range of issues to be addressed in the *Environmental Impact Statement* and identifying the significant issues related to a proposed action. Issues important to the public and local, state, and Federal agencies are solicited through direct mailing, public notices, or meetings. Scoping is generally conducted before development of the *Environmental Impact Statement* scope of work.

Single event - One noise event. For many kinds of analysis, the *sound* from single events is expressed using the *Sound Exposure Level* metric.

Slant-range distance - The distance along a straight line between an aircraft and a point on the ground.

Sound - Sound is the result of vibration in the air. The vibration produces alternating bands of relatively dense and sparse particles of air, spreading outward from the source in the same way as ripples do on water after a stone is thrown into it. The result of the movement is fluctuation in the normal atmospheric pressure or sound waves.

Sound Exposure Level (SEL) - A standardized measure of a *single (sound) event*, expressed in *A-weighted decibels*, that takes into account all sound above a specified threshold set at least ten *decibels* below the maximum level. All sound energy in the event is integrated over one second.

Special Use Airspace - Airspace of defined dimensions identified by an area on the earth's surface wherein activities must be confined because of their nature and/or wherein limitations may be imposed upon aircraft *operations*, which are not part of those activities.

Stage 2 Aircraft - Aircraft that meet the noise levels prescribed by *Federal Aviation Regulations* 14 CFR Part 36, which are less stringent than those established for the quieter **Stage 3** designation. The Airport Noise and Capacity Act required the phase-out of all Stage 2 aircraft over 75,000 pounds by December 31, 1999, with the potential for case-by-case exceptions through the year 2003.

Stage 3 Aircraft - Aircraft that meet the most stringent noise levels set in *Federal Aviation Regulations* 14 CFR Part 36.

Standard Instrument Departure Procedure (SID) - A planned *Instrument Flight Rules air traffic control* departure procedure published for pilot use in graphic and textual form. SIDs provide transition from the terminal to the en route *air traffic control* structure.

Statute Mile - A measure of distance equal to 5,280 feet.

Terminal Radar Approach Control (TRACON) - A *Federal Aviation Administration Air Traffic Control* Facility which uses radar and two-way communication to provide separation of air traffic within a specified geographic area in the vicinity of one or more airports.

Terminal Radar Service Area (TRSA) - Airspace surrounding certain airports where *Air Traffic Control* provides radar *vectoring*, sequencing, and separation on a full-time basis for all *Instrument Flight Rules* and participating *Visual Flight Rules* aircraft.

Time Above (TA) - The amount of time that *sound* exceeds a given *decibel* level during a 24-hour period (e.g., time in minutes that the sound level is above 75 *decibels*).

Thrust Settings – Settings on an aircraft that control the power applied to the engines.

Traffic Pattern – The traffic flow prescribed for aircraft landing at, taxiing on, or taking off from an airport. The components of a typical traffic pattern are *upwind leg, crosswind leg, downwind leg, base leg, and final approach*.

Turbojet - An aircraft powered by a jet turbine engine. The term is customarily used in *air traffic control* for all aircraft, without propellers, that are powered by variants of jet engines, including turbofans.

Turboprop - Aircraft of this type are typically used by airlines on short routes between two relatively close locations.

Upwind Leg - A flight path parallel to the approach runway in the direction of approach.

Vector - Compass heading instructions issued by *Air Traffic Control* in providing navigational guidance by radar.

Very High Frequency Omnidirectional Range (VOR) Station - A ground-based radio navigation aid transmitting signals in all directions. A VOR provides *azimuth* guidance to pilots by reception of electronic signals.

Very High Frequency Omnidirectional Range Station with Tactical Air Navigation (VORTAC) - A navigational aid providing *VOR azimuth* and *Tactical Air Navigation distance measuring equipment* at one site.

Visual Approach - An approach conducted on an *Instrument Flight Rules* flight plan, which authorizes the pilot to proceed visually and clear of clouds to the airport.

Visual Approach Slope Indicator (VASI) - A visual aid for final approach to the *runway threshold*, consisting of two wing bars of lights on either side of the runway. Each bar produces a split beam of light - the upper segment is white, the lower is red.

Visual Flight Rules (VFR) - Rules and procedures specified in *Federal Aviation Regulations* 14 CFR Part 91 for aircraft operations under visual conditions. Aircraft operations under VFR are not generally under *positive control* by *Air Traffic Control*. The term VFR is also used in the U.S. to indicate weather conditions that are equal to or greater than minimum VFR requirements. In addition, it is used by pilots and controllers to indicate a type of flight plan.

Visual Meteorological Conditions (VMC) - Weather conditions expressed in terms of visibility, distance from cloud, and cloud ceiling equal to or greater than those specified in *Federal Aviation Regulations* 14 CFR Part 91.155 for aircraft operations under *Visual Flight Rules*.

Yearly Day-Night Average Sound Level - see *DNL*.

THIS PAGE INTENTIONALLY LEFT BLANK